



PLP380



PLP360



PLP118

Description

For use in under cabinet, bookcase and display cabinet lighting. Long lasting LEDs – 50,000 hours average lamp life. A compact 1" profile, available in a variety of finishes. These LED fixtures can be recessed or surface mounted. The fixture requires a UL listed electronic transformer, plug-in / in line type; 12V maximum (sold separately – see accessories below). The fixture is ETL listed to US and Canadian safety standards.

Catalog Number	LED Color	LEDs	Watts	Finish	Lens	Dimensions
PLP380	W-White WW-Warm White	3 x 1W	3W	WH-White BL-Black NK-Nickel BR-Brass CH-Chrome	C-Clear	Recessed 2.81" Dia. x .03"D Surface Mount 2.81" Dia. X 1.08"D
PLP360	W-White WW-Warm White	3 x 1W	3W	WH-White BL-Black NK-Nickel BR-Brass CH-Chrome	F-Frosted	Recessed 2.81" Dia. x .03"D Surface Mount 2.81" Dia. X 1.08"D
PLP118	W-White WW-Warm White	18	1.4W	WH-White BL-Black NK-Nickel BR-Brass CH-Chrome	C-Clear F-Frosted	Recessed 2.81" Dia. x .03"D Surface Mount 2.81" Dia. X 1.08"D

Accessories
XFR-PLP-12 12V DC Electronic Transformer

Ordering Example: PLP118-WW-CH-F