









Applications:

- Signage and Displays
- Detailed Accenting
- Chandelier Lighting
- Outdoor Perimeter Lighting
- Can follow curved and angular designs



| Catalog No. | Profile | Description | Color |
|-------------|--|--|---|
| 325 |  5/16" OD | Polycarbonate – flexible. Suitable for surface mount. Can be formed to follow curved and angular designs. 6" minimum radius. | Clear |
| 350 |  1/4" 5/16" | Polycarbonate – semi flexible. For recess and surface applications, or under steps. Can be formed to follow curved or angular designs. 12" minimum radius. | Clear, Amber, Blue, Coral, Fuchsia, Grape, Green, Magenta, Red, Smoke, Teal |
| 500 |  1/2" OD | Polycarbonate – rigid. For chandelier and outdoor perimeter lighting. | Clear |
| 338 |  3/8" 3/8" | Polycarbonate – rigid. Suitable for flush floor mounting. Aluminum extrusions accept this profile. | Clear |
| 340 |  5/16" OD | Vinyl – extremely flexible. Suitable for signage, detailed accenting and displays. | Clear |
| 502 |  1/2" OD | Vinyl – extremely flexible. Suitable for signage, detailed accenting and displays | Clear |
| LMH-5 |  | Clip used with tube profiles 325, 340, and 350. Pre-drill for screw attachment. | |
| LMH-R | | | |
| SMH-1 |  | Strap used with tube profiles 325, 380, and 500. | |
| SMH-5 | | | |
| SMH-R | | | |

Specifications:

Polycarbonate

Casing: Polycarbonate, transparent UV stabilized

Color: Clear

UL Flammability Rating: 94V-2

Wiring: Parallel or Series

Conductor: CU, 24AWG

Insulation Material: SPN Clear

Vinyl

Casing: Vinyl, transparent UV stabilized

Color: Clear

UL Flammability Rating: FR-1

Wiring: Parallel or Series

Conductor: Silver Plated CU, 24AWG

Insulation Material: SPN Clear

Lamps:

| Voltage | Design Size | Design Volt | Avg. Amps | Filament M.S.C.P. | Lamp Shape | Hours |
|------------|-------------|-------------|-----------|-------------------|------------|--------|
| 12 Volt DC | LED* | 12.0 | N/A | N/A | 3mm | 60,000 |
| 12 Volt AC | T-1 | 14.0 | .04 | .15 | C-2F | 16,000 |
| 24 Volt AC | T-1 | 5.0 | .115 | .15 | C-2R | 40,000 |

| Operating Voltage 12Volt T-1 Standard Lamp Spacing | | | Operating Voltage 24Volt T-1 Standard Lamp Spacing | | |
|---|------------|--------------|---|------------|--------------|
| Lamp Spacing | Single Run | Watt Per Ft. | Lamp Spacing | Single Run | Watt Per Ft. |
| 1" o.c. | 6'6" | 6 | 1" o.c. | 9' | 6 |
| 2" o.c. | 13' | 3 | 2" o.c. | 18' | 3 |
| 3" o.c. | 20' | 2 | 3" o.c. | 27' | 2 |
| 4" o.c. | 26' | 1.5 | 4" o.c. | 36' | 1.5 |
| 6" o.c. | 40' | 1 | 6" o.c. | 54' | 1 |
| 12" o.c. | 40' | 5 | 12" o.c. | 60' | 5 |

Max. runs 40ft. or 80 lamps, whichever occurs first.

Max. runs 60ft. or 108 lamps, whichever occurs first.

#24GA stranded wire lead
Hard wired

| LED Color | Watts per Lamp | Mcd | Color Temp. |
|------------|----------------|-------|-------------|
| Warm White | .24 | 7,500 | 4000K |

* Light Strands in LED not available in 1" o.c.

